

ROKWEAR®

WE PROTECT

PRODUCT DATASHEET

CLASS: 3

HI-VIS: WATERPROOF JACKETS

PRODUCT DESCRIPTION

A heavyweight stormcoat featuring a quilted lining, waterproof outer fabric, and fleece-lined collar. Designed to provide maximum warmth and protection during harsh weather conditions.

SELBORNE
HI-VIS STORMCOAT

PRODUCT CODE: OHV.3058

FUNDAMENTALS

COMPOSITION
PU coated 300D polyester

FABRIC WEIGHT
425GSM

PRODUCT FEATURES

- Fleece lined collar
- Velcro storm flap
- Phone pocket

TOP BENEFITS

- Waterproof
- Quilted
- Branding

SIZE
S - 5XL

WEIGHT
1.15kg

BOX QUANTITY*
10

SIZE GUIDE

Allowance built in for comfort and to allow the garment to be worn over light layers of clothing.

SIZE:	CHEST SIZE:
XS	91.5cm - 96.5cm
S	96.5cm - 101.5cm
M	101.5cm - 106.5cm
L	106.5cm - 111.5cm
XL	111.5cm - 117cm
2XL	117cm - 122cm
3XL	132cm - 137cm
4XL	142cm - 147cm
5XL	152cm - 157.5cm
6XL	162.5cm - 167.5cm

Indicates how many units are boxed together for shipment from the factory to our warehouse. This does not reflect the quantity received when ordering one unit.

CONFORMS TO

SATRA

EN ISO 20471: 2013+A1: 2016: **CLASS 3**

EN 343: 2019: **3:1 X**

RAIL INDUSTRY STANDARD **RIS-3279-TOM**

COMPONENTS

FABRIC:
100% 190t polyester

FABRIC LINING/STITCHING:
50gsm 100% polyester taffeta

SLEEVE/HOOD:
Internal ribbed cuff, turned back hem 2cm / pack away hood with taped seam

COLLAR:
100% polyester fleece 240gsm

REFLECTIVE TAPE:
100% polyester

FURTHER INFORMATION

HYDROSTATIC HEAD LEVEL:
5500MM

SCAN ME

YOUR GUIDE TO UNDERSTANDING WATERPROOF CLOTHING RATINGS AND STANDARDS

ROKWEAR®

GET IN TOUCH WITH US
Call: +44 (0) 330 441 3500
E-mail: uksales@rokwear.com

HYDROSTATIC HEAD RATING

A hydrostatic head rating is a measure of how waterproof a certain fabric is; this indicates the amount of pressure the material can withstand before it starts to leak through. This test is measured in millimetres (MM), which refers to the height of a column of water that the fabric can resist.

In the UK, waterproof workwear must comply with the BS EN 343 standard, which ensures the safety of workers exposed to rain by addressing both water penetration resistance and breathability.

Class	Waterproof rating (mmH20)	Performance
Class 2	> 800MM	Basic water resistance
Class 3	> 8,000MM	Medium waterproof
Class 4	> 13,000MM	Highly waterproof

STORAGE

Always store in clean, dry conditions. Do NOT store in places subject to direct, strong sunlight.

DISPOSAL

Please dispose of this garment in a responsible safe manner.

AFTERCARE

The washing instructions relate to the Retro Reflective Tape performance and Chromaticity of the background after the stated number of washing cycles and not the waterproofness after washing.



CERTIFIED WASH CYCLES: **25**

Do not wash in biological powder

Machine wash warm or warm hand wash. Do not bleach. Do not iron. Do not dry clean. Do not tumble dry.

Cold rinses, short spin, do not wring.

The stated maximum number of cleaning cycles is not the only factor related to the lifetime of the garment. The lifetime will also depend on usage, care and storage. If damaged, do not repair.

RECOMMENDATIONS FOR WEARING TIME

Temperature of working environment °C	1 R_{et} above 40
25	60 minutes
20	75 minutes
15	100 minutes
10	240 minutes
5	no limit

Always wear the garment fastened.

KEEP CLEAN: Should the High Visibility properties of this garment become unrecoverable soiled or contaminated, replace the item with a new one.

Declarations of Conformity available at www.rokwear.com on product page.

SPECIAL FEATURES

- **FLEECE LINED HIGH STAND COLLAR**
- **FULL LENGTH VELCRO FASTENED STORM FLAP**

STANDARDS

UK CA CE

These garments comply with the requirements of PPE Regulation (EU) 2016/425 and PPE Regulation (EU) 2016/425 as retained in UK law and amended.

EN ISO 20471:2013+A1:2016

EN ISO 13688:2013+A1:2021

Class 3 area of high visibility orange/ fluorescent yellow background and retro reflective tape. Two bands of retro reflective material around torso and each sleeve, one band over each shoulder.

EN 343:2019

Class 1 - 4 (4 highest water penetration).
Class 1 - 4 (4 highest water vapour resistance).
Rain Tower 'X' not tested.

RIS-3279-TOM ISSUE 2:2019

SATRA

Notified Body: SATRA Technology Europe Ltd
Bracetown Business Park
Clonee. Co. Meath D15 YN2P Ireland
Notified Body No. 2777

Country of origin: China
Commodity code: 6203331000

OHV.3058