

FIRECHIEF® XTR ABC POWDER EXTINGUISHERS

FIRECHIEF®
making the world a safer place

MODEL:

FMP1 **FXP6**
FXP2 **FXP9**
FXP3 **FXP12**
FXP4



FXP6
100-1179

FXP9
100-1190

FXP12
100-1161



FMP1
100-1046

FXP2
100-1162

FXP3
100-1171

FXP4
100-1175

- Kitemark and LPCB approved certified to EN3
- MED approved
- 35Kv Dielectric tested
- 5 year guarantee
- Designed, developed and tested in UK
- Squeeze grip operation
- Internal polyethylene lining
- Multi-purpose application
- Corrosion resistant finish
- Wire mounting bracket supplied with FMP1, FXP2
- Wall mounting bracket supplied with FXP3, 4, 6, 9 and 12



KM 558897
BS EN 3



Certified to EN3
LPCB Ref: 1093a



8516



0029



+44 (0) 330 999 0019



sales@firechiefglobal.com



firechiefglobal.com

FIRECHIEF® XTR ABC POWDER EXTINGUISHERS

FIRECHIEF®
making the world a safer place

The Firechief® XTR range of Dry Powder Extinguishers are a highly versatile Class A, B and C fire-fighting medium for most fire risks. In addition to dealing with electrical hazards, flammable liquids and gases, general wood/paper fires, this extinguisher is also effective on vehicle fires.

MODEL:

FMP1
FXP2
FXP3
FXP4

FXP6
FXP9
FXP12



Specifications

Model	FMP1	FXP2	FXP3	FXP4	FXP6	FXP9	FXP12
Product Code	100-1046	100-1162	100-1171	100-1175	100-1179	100-1190	100-1161
Description	Firechief® 1kg ABC Powder Extinguisher	Firechief® XTR 2kg Powder Extinguisher	Firechief® XTR 3kg Powder Extinguisher	Firechief® XTR 4kg Powder Extinguisher	Firechief® XTR 6kg Powder Extinguisher	Firechief® XTR 9kg Powder Extinguisher	Firechief® XTR 12kg Powder Extinguisher
Capacity (kg)	1	2	3	4	6	9	12
Fire Rating	8A 34B C	13A 89B C	21A 113B C	27A 144B C	43A 233B C	55A 233B C	55A 233B C
MED Approval	Yes	Yes	Yes	Yes	YES	YES	YES
Throw Range (m)	3	3	3	5	5	6	5
Discharge Time (secs)	8	13	15	17	19	26	30
Working Pressure (bar)	15	15	15	15	15	15	15
Temperature Range (°C)	(-30°C+60°C)	(-30°C+60°C)	(-30°C+60°C)	(-30°C+60°C)	(-30°C+60°C)	(-30°C+60°C)	(-30°C+60°C)
Product Height (mm)	327	383	435	484	531	551	663
Product Diameter (mm)	85	110	130	130	154	182	190
Filled Weight (kg)*	1.8	3.5	4.9	6.2	8.9	13.3	17.5
Carton Height (mm)	338	414	458	518	570	586	718
Carton Length (mm)	108	154	150	154	180	206	214
Carton Width (mm)	106	122	144	150	176	194	200
Packaged Weight (kg)**	2	3.7	5.3	6.8	9.6	13.9	17.9
Product EAN	5055377900274	5055377900373	5055377900069	5055377900076	5055377900380	5055377900397	5055377900106

* Extinguisher, contents and plastic base only (where applicable) - not including hose, bracket or packaging.

** Includes all packaging, hose / horn and bracket.

Imported into EU by: Firechief® Global (EU) Ltd, 3rd Floor, 40 Mespil Road, Dublin 4, D04 C2N4, Ireland

For more information contact: Firechief® Global, 3 Lands End Way, Oakham, Rutland, LE15 6RB, UK | UK: 0330 999 0019 | International: +44 (0)1572 772657 | www.firechiefglobal.com/contact-us/

 +44 (0) 330 999 0019

 sales@firechiefglobal.com

 firechiefglobal.com